



# LR6-60PB 285~305M



## Hi-MO1 High Efficiency Low LID Mono PERC Technology (60C/All Black Module)

*Aesthetic appearance with black frame and  
backsheet, best suited for rooftop installation*

10-year Warranty for Materials and Processing;  
25-year Warranty for Extra Linear Power Output



**-0.55%**

25-year Power  
Warranty Annual  
Power Attenuation  
-0.55%

**+4.10%**

### Complete System and Product Certifications

IEC 61215, IEC61730, UL1703  
ISO 9001:2008: ISO Quality Management System  
ISO 14001: 2004: ISO Environment Management System  
TS62941: Guideline for module design qualification and type approval  
OHSAS 18001: 2007 Occupational Health and Safety



\* Specifications subject to technical changes and tests. LONGi Solar reserves the right of interpretation.

**Positive power tolerance** (0 ~ +5W) guaranteed

**High module conversion efficiency** (up to 18.7%)

**Slower power degradation** enabled by Low LID Mono PERC technology: first year <2%, 0.55% year 2-25

**Better energy yield** with excellent low irradiance performance and temperature coefficient

**Solid PID resistance** ensured by solar cell process optimization and careful module BOM selection

**Adaptable to harsh environment:** passed rigorous salt mist and ammonia tests

**Robust frame** (40mm) withstands mechanical loading of 5400Pa for snow load on front and 2400Pa for wind load on rear side


# LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203  
Tel: + 86-21-61047332 Fax: +86 21- 61047377 E-mail: module@longi-silicon.com  
Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.

# LR6-60PB 285~305M

## Design (mm)



## Mechanical Parameters

Cell Orientation: 60 (6×10)  
 Junction Box: IP67, three diodes  
 Output Cable: 4mm<sup>2</sup>, 1000mm in length  
 Connector: MC4 or MC4 compatible  
 Weight: 18.2kg  
 Dimension: 1650×991×40mm  
 Packaging: 26pcs per pallet

## Operating Parameters

Operational Temperature: -40 C ~ +85 C  
 Power Output Tolerance: 0 ~ +5 W  
 Maximum System Voltage: DC1000V (IEC)  
 Maximum Series Fuse Rating: 15A  
 Nominal Operating Cell Temperature: 45±2 C  
 Application Class: Class A

## Electrical Characteristics

Model Number	LR6-60PB-285M		LR6-60PB-290M		LR6-60PB-295M		LR6-60PB-300M		LR6-60PB-305M	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Testing Condition										
Maximum Power (Pmax/W)	285	209.5	290	213.2	295	216.8	300	220.5	305	224.2
Open Circuit Voltage (Voc/V)	39.5	36.5	39.7	36.7	39.9	36.9	40.1	37.1	40.2	37.2
Short Circuit Current (Isc/A)	9.46	7.62	9.58	7.72	9.69	7.81	9.81	7.91	9.94	8.01
Voltage at Maximum Power (Vmp/V)	32.1	29.5	32.3	29.7	32.6	29.9	32.8	30.1	33.0	30.3
Current at Maximum Power (Imp/A)	8.88	7.10	8.98	7.18	9.05	7.24	9.15	7.32	9.24	7.39
Module Efficiency(%)	17.4		17.7		18.0		18.3		18.7	

STC (Standard Testing Conditions): Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25 C, Spectra at AM1.5

NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20 C, Spectra at AM1.5, Wind at 1m/s

## Temperature Ratings ( STC )


Temperature Coefficient of Isc	+0.057%/C
Temperature Coefficient of Voc	-0.286%/C
Temperature Coefficient of Pmax	-0.380%/C

## Mechanical Loading


Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

## I-V Curve


Current-Voltage Curve (LR6-60PB-300M)



Power-Voltage Curve (LR6-60PB-300M)



Current-Voltage Curve (LR6-60PB-300M)



# LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203  
 Tel: + 86-21-61047332 Fax: +86 21- 61047377 E-mail: module@longi-silicon.com  
 Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.