







Plug and play installation.



Strong WiFi signal for maximum range.



Suitable for outdoor installation.



Remote Monitoring

Connect to the

The Smart WiFi 2.0 is an intelligent WiFi enabled device allowing you to monitor the status and performance of your FoxESS PV system via the FoxCloud remote monitoring platform.

System owners and installers can easily keep up-to-date with performance data in real-time, view historic records and monitor system alerts.

- Stable wireless communication
- IP65 protection class
- Wide operating temperature range
- Clean and compact design
- User-friendly monitoring app
- Plug and play installation
- Monitor your system from anywhere
- 24/7 monitoring











Fox SMART WIFI SMART WIFI 2.0

| SPECIFICATIONS | |
|----------------------------------|--------------------------------|
| Product Name | Smart WiFi 2.0 |
| Working Voltage | DC7~12V |
| Average Power Consumption (W) | 1 |
| Operating Temperature Range (°c) | -20~60 |
| Storage Temperature Range (°c) | -20~60 |
| Antenna Gain | 3dB |
| Frequency Range | 2.400~2.472GHz |
| Data Interface | UART: 9600/8/n/1 |
| User Configuration Interface | DHCP/Static IP/Firmware Upload |
| Protection Level | IP65 |
| Data Upload Interval | 5 minutes |
| Weight (Kg) | 0.05 |
| Dimensions (L*W*H) (mm) | 105*50*26.5 |
| Communication Method | RS485 |

